



ASF Series Bearing Modifications

PART	A	B	C	D	E	F	G	BALLS NO.	DIA.	RADIAL LOAD RATING (LBS.) AT			
										50 RPM	100 RPM	600 RPM	1200 RPM
ASF-175-3B	.906 - .911	.313 - .317	1/4	1/16	1/8	1 1/32	25/64	16	1/8	180	110	60	40
ASF-175-2B	.906 - .911	.313 - .317	1/4	1/16	1/8	1 1/32	7/16	16	1/8	180	110	60	40
ASF-175-4B	.906 - .911	.375 - .380	1/4	1/16	1/8	1 1/32	11/16	16	1/8	180	110	60	40
ASF-175-1H	.906 - .911	.376 - .380	1/4	1/16	1/8	1 1/32	0.365	16	1/8	180	110	60	40
ASF-132-2R	1.125 - 1.130	.376 - .380	5/16	5/64	1/8	1 1/4	43/64	13	3/16	215	150	100	60
ASF-132-1X	1.125 - 1.130	.380 - .385	5/16	5/64	1/8	1 1/4	39/64	13	3/16	215	150	100	60
ASF-132-6R	1.125 - 1.130	.438 - .442	5/16	5/64	0.364	1 1/4	0.417	13	3/16	215	150	100	60
ASF-132-5R	1.125 - 1.130	.438 - .442	5/16	5/64	0.105	1 1/4	0.668	13	3/16	215	150	100	60
ASF-132-1R	1.125 - 1.130	.438 - .442	5/16	5/64	1/8	1 1/4	1	13	3/16	215	150	100	60
ASF-132-1AB	1.125 - 1.130	.500 - .504	5/16	5/64	1/8	1 1/4	39/64	13	3/16	215	150	100	60
ASF-132-1AC	1.125 - 1.130	.500 - .504	5/16	5/64	0.088	1 1/4	21/32	13	3/16	215	150	100	60
ASF-132-3C	1.125 - 1.130	.501 - .503	5/16	5/64	3/16	1 1/4	5/8	13	3/16	215	150	100	60
ASF-107-7N	1.375 - 1.380	.376 - .380	5/16	5/64	5/16	1 1/2	9/16	17	3/16	390	270	180	108
ASF-107-4N	1.375 - 1.380	.500 - .504	5/16	5/64	3/16	1 1/2	11/16	17	3/16	390	270	180	108
ASF-107-5N	1.375 - 1.380	.500 - .504	5/16	5/64	5/16	1 1/2	9/16	17	3/16	390	270	180	108
ASF-107-1W	1.375 - 1.380	.515 - .520	5/16	5/64	1/8	1 1/2	7/8	17	3/16	390	270	180	108
ASF-107-2N	1.375 - 1.380	.625 - .629	5/16	5/64	1/8	1 1/2	1 1/16	17	3/16	390	270	180	108