



PA Series Bearing Modifications

PART	A	B	C	D	E	F	G	RADIAL LOAD RATING (LBS.) AT							
								BALLS		50	100	300	600	800	1000
								NO.	DIA.	RPM	RPM	RPM	RPM	RPM	RPM
PA-715-2A	.905 - .908	.251 - .255	1/4	1/16	1/8	1 1/32	9/16	12	5/32	75	54	39	30	26.4	23.4
PA-715-3A	.905 - .908	.251 - .255	1/4	1/16	1/8	1 1/32	7/16	12	5/32	75	54	39	30	26.4	23.4
PA-715-2E	.906 - .911	.251 - .255	1/4	1/16	1/8	1 1/32	25/64	12	5/32	75	54	39	30	26.4	23.4
PA-715-1E	.906 - .911	.251 - .255	1/4	1/16	1/8	1 1/32	11/32	12	5/32	75	54	39	30	26.4	23.4
PA-715-4A	.905 - .908	.313 - .317	1/4	1/16	1/8	1 1/32	7/16	12	5/32	75	54	39	30	26.4	23.4
PA-641-1M	1.125 - 1.130	.251 - .255	5/16	5/64	7/64	1 1/4	29/64	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-5A	1.125 - 1.130	.251 - .255	5/16	5/64	1/8	1 1/4	1/2	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-2M	1.125 - 1.130	.313 - .317	5/16	5/64	7/64	1 1/4	29/64	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-4A	1.125 - 1.130	.313 - .317	5/16	5/64	1/8	1 1/4	5/8	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-4G	1.125 - 1.130	.313 - .317	5/16	5/64	5/32	1 1/4	21/32	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-3C	1.125 - 1.130	.375 - .380	5/16	5/64	1/8	1 1/4	21/64	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-684-2	1.125 - 1.130	.375 - .380	5/16	5/64	1/8	1 1/4	3/4	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-684-4	1.125 - 1.130	.375 - .380	5/16	5/64	1/8	1 1/4	11/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-3G	1.125 - 1.130	.376 - .380	5/16	5/64	5/32	1 1/4	21/32	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-3M	1.125 - 1.130	.376 - .380	5/16	5/64	11/64	1 1/4	41/64	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-3A	1.125 - 1.130	.376 - .380	5/16	5/64	1/8	1 1/4	5/8	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-3B	1.125 - 1.130	.376 - .380	5/16	5/64	13/64	1 1/4	9/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-2G	1.125 - 1.130	.376 - .380	5/16	5/64	5/32	1 1/4	21/32	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-684-5	1.125 - 1.130	.438 - .442	5/16	5/64	1/8	1 1/4	11/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-1F	1.125 - 1.130	.439 - .443	5/16	5/64	7/64	1 1/4	3/8	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-1N	1.125 - 1.130	.500 - .505	5/16	5/64	3/8	1 1/4	7/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-684-1	1.125 - 1.130	.500 - .505	5/16	5/64	1/8	1 1/4	11/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-684-3	1.125 - 1.130	.500 - .505	5/16	5/64	1/8	1 1/4	3/4	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-800-1	1.125 - 1.130	.501 - .504	5/16	5/64	11/32	1 1/4	3/4	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-877-1	1.125 - 1.130	.501 - .504	5/16	5/64	1/8	1 1/4	9/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-668-1	1.125 - 1.130	.502 - .506	5/16	5/64	1/2	1 1/4	13/16	13	3/16	107.5	77.4	55.9	43	37.84	33.54
PA-641-1G	1.125 - 1.130	.505 - .509	5/16	5/64	7/32	1 1/4	19/32	13	3/16	107.5	77.4	55.9	43	37.84	33.54